

DECLARATION OF PERFORMANCE

No: 005

1. Unique identification code of the product

DRY-PRESSED CERAMIC TILES, WITH WATER ABSORTION $E \leq 0.5\%$, TYPE 5

2. Intended use

FOR INTERNAL AND EXTERNAL WALLS AND FLOORINGS

3. Name and adress of Manufacturer

BALDOCER, S.A.
Ctra. La Pobla Tornesa – Vall d’Alba, km.4
12192 Vilafamés (Castellón) SPAIN

4. Systems of AVCP: System 4

5. Harmonised standard: EN 14411: 2012

6. Declared performances

ESSENTIAL CHARACTERISTICS	PERFORMANCES
Reaction to fire	A1-A1 _{FL}
Release of dangerous substance, for: - Cadmium - Lead - Others	NPD
Breaking strength	≥ 1300 N
Slipperiness, as: PTV (wet) slider 57, CEN/TS 16165:2012 Annex C	NPD
Bond strength/adhesion, for: - Cementitious adhesives - Dispersion adhesives - Reaction resin adhesives - Mortar	Type C2: > 1 N/mm ² NPD NPD NPD
Thermal shock	Pass
Durability for: - Internal use - External Use: freeze-thaw resistance	Pass Pass
Tactility	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of conformity is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Felipe Peraire Palos
General Manager

Vilafamés, October 8th 2020