
		PRODUCT INFORMATION SHEET (ANNEX 5)		Creation date (dd/mm/yyyy) :	2022/1/7	
				Last update date (dd/mm/yyyy) :	2022/1/7	
1	General information	Supplier's name or trade mark		LEXMAN		
2		Supplier's address		ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN		
3		Model Identifier - Luminaire Supplier reference		T25 15W SB		
4		Light sources maker model		T25 15W SB		
5		Date of placement on the market		1/9/2021		
6	Type of light source:	Lighting technology used:		other		
7		Light source cap type (or other electric interface)		E14		
8		Non-directional (NDLS) or directional (DLS):		NDLS		
9		Mains (MLS) or non-mains (NMLS):		MLS		
10		Connected light source (CLS):		no		
11		Colour-tuneable light source:		no		
12		Envelope:		no		
13		High luminance light source:		no		
14		Anti-glare shield:		no		
15		Dimmable:		yes		
16	General product parameters:	Energy consumption in on-mode (kWh/1000 h)		15	KWh/1000h	
17		Energy efficiency class		G		
18		Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in Lm		80	360	
19		Correlated colour type		single value		
20		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set		2200	K	
21		On-mode power (P_{on}), expressed in W and rounded to the first decimal		15.0	W	
22		Standby power (P_{sb}), expressed in W and rounded to the second decimal		0.00	W	
23		Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal		0.00	W	
24		Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set		100		
25		Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre)				
26		Height (mm)		56.00	mm	
27		Width (mm)		25.00	mm	
28		Depth (mm)		25.00	mm	
29		Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpeg))		T25 15W SB-spectral power distribution.jpg 		
30		Claim of equivalent power				
31		If yes, equivalent power (W)		W		
32		Chromaticity coordinates (x and y)		CCx=0.506, CCy=0.415		
33	Parameters for directional light sources:	Peak luminous intensity (cd)		cd		
34		Beam angle in degrees (no decimal), or the range of beam angles that can be set		Degrees		
35	Parameters for LED and OLED light sources:	R9 colour rendering index value				
36		Survival factor rounded to the second decimal (>0.xx)				
37		Lumen maintenance factor rounded to the second decimal (>0.xx)				
38	Parameters for LED and OLED mains lights sources:	displacement factor (cos ϕ_1) rounded to the second decimal				
39		Colour consistency in McAdam ellipses				
40		Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.				
41		If yes then replacement claim (W) (no decimal)		W		
42		Flicker metric (Pst LM) rounded to the first decimal				
43		Stroboscopic effect metric (SVM) rounded to the first decimal				
44	Technical documentation name (in case of light source product)		T25 15W SB-Technical documentation for light source.pdf			
45	Light source removing instruction name (in case of containing product)					