Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier	's name or	trade marl	k: EGLO
----------	------------	------------	---------

Supplier's address: EGLO Leuchten GmbH, Heiligkreuz 22, 6136 Pill, AT

Model identifier: 2835-L387-144-38W-2700K-6500K

Tvi	рe	of	lig	ht	SO	urce	:
. , ,		•	о		-		•

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	-				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					
Parameter	Value	Parameter	Value		

Froduct parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption mode (kWh/1000 h), up to the nearest integ	rounded	38	Energy efficiency class	С		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		6 600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500		
On-mode power (P _{on}), expressed in W		38,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen- sions without Width separate con- trol gear, light- ing control	1	1 352 387	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	357		
		Chromaticity coordi-	0,315		
		nates (x and y)	0,337		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	0	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;



