


EAN	3276007607079
Supplier's name or trade mark	LEXMAN
Date of placement on the market (YYYY-MM-DD)	2023-06-01
Light sources maker model	E162085682205
EPREL Registration number	1424934
Link to EU Product Data base	https://eprel.ec.europa.eu/screen/product/lightsources/1424934
Lighting technology used	LED
Non-directional (NDLS) or directional (DLS)	NDLS
Light source cap-type	E27
Mains (MLS) or non-mains (NMLS)	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
High luminance light source	No
Anti-glare shield	No
Dimmable	no
Energy consumption in on-mode (kWh/1000h)	5
Useful luminous flux (lm)	400
Beam angle correspondence (degrees)	360
Energy Efficiency Class	G
Correlated colour temperature type (K)	single value
Correlated colour temperature (K)	2200
On-mode power (W)	4.9
Standby power (W)	0.00
Colour rendering index	80
Outer dimensions (Height) (millimetre)	285
Outer dimensions (Width) (millimetre)	160
Outer dimensions (Depth) (millimetre)	160
Spectral power distribution in the range 250 nm to 800 nm. at full-load	 <p>The graph displays the spectral power distribution (SPD) for the light source. The x-axis represents the wavelength in nanometers (nm), ranging from 250 to 800 nm. The y-axis represents the relative power, ranging from -0.01 to 0.80. The SPD curve shows a small peak around 450 nm and a much larger, broader peak centered at approximately 600 nm, reaching a maximum relative power of about 0.75. The power drops to near zero by 800 nm.</p>
Spectral power distribution (picture name)	Spectral Power Distribution - E162085682205. jpg
Claim of equivalent power	Yes
Equivalent power (W)	35
Chromaticity coordinate (x)	0.502
Chromaticity coordinate (y)	0.415
R9 Colour rendering index	1
Survival factor	0.90
Lumen maintenance factor	0.96
Displacement factor	-
Colour consistency in McAdam ellipses	5
Flicker metric	0.0
Stroboscopic effect metric	0.0
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage	NO