


|                                                                                   |                                                                        |                                                                                                                                                                 |                                                                                     |                                 |        |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------|--------|
|  |                                                                        | <b>PRODUCT INFORMATION SHEET (ANNEX 5)</b>                                                                                                                      |                                                                                     | Creation date (dd/mm/yyyy) :    | 8/2023 |
|                                                                                   |                                                                        |                                                                                                                                                                 |                                                                                     | Last update date (dd/mm/yyyy) : | 8/2023 |
| 1                                                                                 | General information                                                    | Supplier's name or trade mark                                                                                                                                   | SENSEA                                                                              |                                 |        |
| 2                                                                                 |                                                                        | Supplier's address                                                                                                                                              | ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN                         |                                 |        |
| 3                                                                                 |                                                                        | Model Identifier - Luminaire Supplier reference                                                                                                                 | MFT8070TC ( 2024R07P04-0009 )                                                       |                                 |        |
| 4                                                                                 |                                                                        | Light sources maker model                                                                                                                                       | ESSENTIAL                                                                           |                                 |        |
| 5                                                                                 |                                                                        | Date of placement on the market                                                                                                                                 |                                                                                     |                                 |        |
| 6                                                                                 | Type of light source:                                                  | Lighting technology used:                                                                                                                                       | LED                                                                                 |                                 |        |
| 7                                                                                 |                                                                        | Light source cap type (or other electric interface)                                                                                                             | No cap-type                                                                         |                                 |        |
| 8                                                                                 |                                                                        | Non-directional (NDLS) or directional (DLS) :                                                                                                                   | NDLS                                                                                |                                 |        |
| 9                                                                                 |                                                                        | Mains (MLS) or non-mains (NMLS) :                                                                                                                               | NMLS                                                                                |                                 |        |
| 10                                                                                |                                                                        | Connected light source (CLS) :                                                                                                                                  | no                                                                                  |                                 |        |
| 11                                                                                |                                                                        | Colour-tuneable light source:                                                                                                                                   | no                                                                                  |                                 |        |
| 12                                                                                |                                                                        | Envelope:                                                                                                                                                       | no                                                                                  |                                 |        |
| 13                                                                                |                                                                        | High luminance light source:                                                                                                                                    | no                                                                                  |                                 |        |
| 14                                                                                |                                                                        | Anti-glare shield:                                                                                                                                              | no                                                                                  |                                 |        |
| 15                                                                                |                                                                        | Dimmable:                                                                                                                                                       | no                                                                                  |                                 |        |
| 16                                                                                | General product parameters:                                            | Energy consumption in on-mode (kWh/1000 h)                                                                                                                      | 14                                                                                  | KWh/1000h                       |        |
| 17                                                                                |                                                                        | Energy efficiency class                                                                                                                                         | E                                                                                   |                                 |        |
| 18                                                                                |                                                                        | Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in Lm | 1848                                                                                |                                 |        |
| 19                                                                                |                                                                        | Correlated colour type                                                                                                                                          | single value                                                                        |                                 |        |
| 20                                                                                |                                                                        | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K,                      | 4000                                                                                | K                               |        |
| 21                                                                                |                                                                        | On-mode power ( $P_{on}$ ), expressed in W and rounded to the first decimal                                                                                     | 13.2                                                                                | W                               |        |
| 22                                                                                |                                                                        | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal                                                                                    |                                                                                     | W                               |        |
| 23                                                                                |                                                                        | Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal                                                                 |                                                                                     | W                               |        |
| 24                                                                                |                                                                        | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                              | 80                                                                                  |                                 |        |
| 25                                                                                |                                                                        | Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre)                                       |                                                                                     |                                 |        |
| 26                                                                                |                                                                        | Height (mm)                                                                                                                                                     | 8.00                                                                                | mm                              |        |
| 27                                                                                |                                                                        | Width (mm)                                                                                                                                                      | 733.00                                                                              | mm                              |        |
| 28                                                                                |                                                                        | Depth (mm)                                                                                                                                                      | 1.00                                                                                | mm                              |        |
| 29                                                                                |                                                                        | Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpeg)  |  |                                 |        |
| 30                                                                                |                                                                        | Claim of equivalent power                                                                                                                                       |                                                                                     |                                 |        |
| 31                                                                                |                                                                        | If yes, equivalent power (W)                                                                                                                                    |                                                                                     | W                               |        |
| 32                                                                                |                                                                        | Chromaticity coordinates (x and y)                                                                                                                              |                                                                                     |                                 |        |
| 33                                                                                | Parameters for directional light sources:                              | Peak luminous intensity (cd)                                                                                                                                    |                                                                                     | cd                              |        |
| 34                                                                                |                                                                        | Beam angle in degrees (no decimal), or the range of beam angles that can be set                                                                                 |                                                                                     | Degrees                         |        |
| 35                                                                                |                                                                        | R9 colour rendering index value                                                                                                                                 | 20                                                                                  |                                 |        |
| 36                                                                                | Parameter for LED and OLED light sources:                              | Survival factor rounded to the second decimal ( $>0.xx$ )                                                                                                       |                                                                                     |                                 |        |
| 37                                                                                |                                                                        | Lumen maintenance factor rounded to the second decimal ( $>0.xx$ )                                                                                              |                                                                                     |                                 |        |
| 38                                                                                | Parameters for LED and OLED mains lights sources:                      | displacement factor ( $\cos \phi_1$ ) rounded to the second decimal                                                                                             |                                                                                     |                                 |        |
| 39                                                                                |                                                                        | Colour consistency in McAdam ellipses                                                                                                                           | 6.0                                                                                 |                                 |        |
| 40                                                                                |                                                                        | Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.                                         |                                                                                     |                                 |        |
| 41                                                                                |                                                                        | If yes then replacement claim (W) (no decimal)                                                                                                                  |                                                                                     | W                               |        |
| 42                                                                                |                                                                        | Flicker metric (Pst LM) rounded to the first decimal                                                                                                            |                                                                                     |                                 |        |
| 43                                                                                |                                                                        | Stroboscopic effect metric (SVM) rounded to the first decimal                                                                                                   |                                                                                     |                                 |        |
| 44                                                                                | Technical documentation name (in case of light source product)         |                                                                                                                                                                 |                                                                                     |                                 |        |
| 45                                                                                | Light source removing instruction name (in case of containing product) |                                                                                                                                                                 |                                                                                     |                                 |        |