


EAN	3276007662337
Product Supplier reference	HT-VOL110-20W
Type of product	Containing product
Supplier's address	ADEO Services - 135 rue Sadi Carnot - CS00001. 59790 RONCHIN
Supplier's name or trade mark	INSPIRE
Replaceability of Light source	non-replacable
Replaceability of separate control gears	by qualified person
Light sources maker model	VOL110-20W-LS
Link to EU Product Data base	<a href="https://eprel.ec.europa.eu/screen/product/light-sources/1842186">https://eprel.ec.europa.eu/screen/product/light-sources/1842186</a>
Spectral power distribution in the range 250 nm to 800 nm. at full-load	 <p>The graph displays the spectral power distribution (SPD) of the light source. The x-axis represents the wavelength in nanometers (nm), ranging from 250 to 1000. The y-axis represents the spectral power, ranging from 0.0 to 1.2. The curve shows a sharp peak in the blue region (around 450 nm) and a broad, multi-colored spectrum in the visible range (400-700 nm), with a maximum power of 1.0 x 10^-12 W/nm.</p>
If the light source contains mercury: instructions on how to clean up the debris in case of accidental breakage	Not Applicable
Recommendations on how to dispose of the light source / Driver at the end of its life Directive 2012/19/EU	Electrical product must not be thrown out with domestic waste. They must be taken to a communal collecting point for environmentally friendly disposal in accordance with local regulations. Contact your local authorities or stockist for advice on recycling.
Driver maker model	VOL-20W
Maximum output power of the driver (for HL, LED and OLED) or the power of the light source for which the driver is intended (for FL and HID);	N/A
Type of light source(s) for which it is intended	N/A
Efficiency in full-load	N/A
No-load power (Pno) (W)	N/A
Standby power (Psb) (W)	N/A
Standby power (Pnet) (W)	N/A
Driver suitable for dimming :	N/A