


| | | | | | |
|-------|---|--|---|---|-----|
| 1-5 | General information | Supplier's name or trade mark | INSPIRE | | |
| | | Supplier's address | ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN | | |
| | | Model Identifier - Luminaire Supplier reference | G18082P(96) | | |
| | | Light sources maker model | G18082-FGL-MZ | | |
| | | Date of placement on the market | 30/06/2023 | | |
| 6-15 | Type of light sources: | Lighting technology used: | LED | | |
| | | Light source cap type (or other electric interface) | / | | |
| | | Non-directional (NDLS) or directional (DLS): | NDLS | | |
| | | Mains (MLS) or non-mains (NMLS): | MLS | | |
| | | Connected light source (CLS): | no | | |
| | | Colour-tunable light source: | no | | |
| | | Envelope: | no | | |
| | | High luminance light source: | no | | |
| | | Anti-glare shield: | no | | |
| | | Dimmable: | no | | |
| 16-32 | General product parameters: | Energy consumption in on-mode (kWh/1000 h) | 11 | kWh/1000h | |
| | | Energy efficiency class | D | | |
| | | Useful luminous flux (Φ_{use}) indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in Lm | 1500lm | | 360 |
| | | Correlated colour type | single value | | |
| | | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4000 | K | |
| | | On-mode power (P_{on}), expressed in W and rounded to the first decimal | 11.0 | W | |
| | | Standby power (P_{st}), expressed in W and rounded to the second decimal | 0.27 | W | |
| | | Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal | 0.00 | W | |
| | | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | >80 | | |
| | | Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre) | | | |
| | | | Height (mm) | 960.00 | mm |
| | | | Width (mm) | 80.00 | mm |
| | | | Depth (mm) | 207.00 | mm |
| | | | Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpeg)) |  G18082P(96)spectral power distribution.jpeg | |
| | | | Claim of equivalent power | yes | |
| | | | If yes, equivalent power (W) | 99 | W |
| | | | Chromaticity coordinates (x and y) | 0.380; 0.380 | |
| 33-35 | Parameters for LED and OLED light sources: | Peak luminous intensity (cd) | | cd | |
| | | Beam angle in degrees (no decimal), or the range of beam angles that can be set | | Degrees | |
| | | R9 colour rendering index value | 1 | | |
| 36-37 | Parameter for LED and OLED light sources: | Survival factor rounded to the second decimal (>0.xx) | 0.9 | | |
| | | Lumen maintenance factor rounded to the second decimal (>0.xx) | 0.96 | | |
| 38-43 | Parameters for LED and OLED mains lights sources: | displacement factor (cos ϕ_1) rounded to the second decimal | 0.92 | | |
| | | Colour consistency in McAdam ellipses | 4.4 | | |
| | | Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | - | | |
| | | If yes then replacement claim (W) (no decimal) | | W | |
| | | Flicker metric (Pst LM) rounded to the first decimal | 0.0 | | |
| | | Stroboscopic effect metric (SVM) rounded to the first decimal | 0.0 | | |
| | | | | | |
| 44 | | Technical documentation name (in case of light source product) | | | |
| 45 | | Light source removing instruction name (in case of containing product) | G18082P(96)_lightsource removing instruction.pdf | | |