

| No. | Name of Parts | Specifications | Unit | Qty | Remark |
|-----|--|--|------|-----|-------------------------------------|
| 1 | G21209 lamp shade | light diffuser PC (CM4272-DHX) Tonggyuan 120H UV | PC | 1 | |
| 2 | M3*6 Eleven-slotted pan head self-extruding screws | hardness 450HV0.3, zinc surface-plating | PC | 4 | fix reflective screen |
| 3 | G21209 reflective screen | ABS757(Titanium dioxide) | PC | 1 | |
| 4 | G21209 clear diffuser | PC S-2000UR(clear) | PC | 1 | |
| 5 | G21209 lamp body | ADC12 | PC | 1 | spray coating |
| 6 | G21209 radiator seal ring | silicone 50° black | PC | 1 | |
| 7 | M3*5 eleven-slotted pan head self-extruding screws | hardness 450HV0.3, zinc surface-plating | PC | 4 | 2pcs fix LED module,2pcs fix driver |
| 8 | G21209-DB PCB | 4000K | PC | 1 | |
| 9 | G21209 radiator | ADC12 | PC | 1 | spray coating |
| 10 | M3*8 cross recessed countersunk head screws | stainless steel 304 | PC | 4 | |
| 11 | G21209-FGL-QD drive input brown blue wire L=90MM stripped wire 9mm and tin immersed output red black wire L=70MM stripped wire 9mm and tin immersed sleeve 2.5 * 30MM heat shrink tube | | PC | 1 | |
| 12 | G21209 mounting plate seal ring | silicone 50° black | PC | 1 | |
| 13 | G21209 mounting plate | PA6+30%GF(black) | PC | 1 | |
| 14 | 17LG2 16476 G06444 protective coil(black) | silicone 50° black | PC | 1 | |
| 15 | M4*8 eleven slot pan head self extrusion screw | hardness 450HV0.3, surface dacromet | PC | 1 | |
| 16 | Ø4 external serrated lock washers | zinc surface-plating | PC | 2 | |
| 17 | Yellow-green grounding wire (Φ4) L=100MM (with letters) stripped 9MM and dipped in tin | H05V-K 0.75mm2 | PC | 1 | |
| 18 | PA10-10-3 bilateral pressing terminal | | PC | 1 | |
| 19 | M5*10 hexagon socket set screws with cone point | stainless steel 304 black | PC | 1 | |
| | ST4.2*30 cross recessed flat head self-tapping screws | stainless steel 304 | PC | 2 | as accessory |
| | φ6*30 plastic expansion | φ6, HDPE | PC | 2 | as accessory |
| | 2.5MM allen wrench | blackened | PC | 1 | as accessory |

