G18082WH BOM

No.	Name of Parts	Specifications	Unit	Qty	Remark	20 19 18 17
1	G18082 Diffuser	PC (CM4272-DH)	PCS	1		21 21 5 2
2	Φ210XΦ3 Foaming silicone ring	Φ3 white Foaming silicone ring	PCS	1		
3	M3+5 Eleven slotted pan head self-squeezing screws	Hardness: 450HV0.3, with zinc surface-plating	PCS	4	To fix the LED module	
4	G18082 M3 screw socket set	PC(white)	PCS	4		
5	G18082-FGL-MZ module	0.4MM PCB, 4000K	PCS	1		
6	G18082 lamp body	ADC12	PCS	1	with powder coating	
7	M5+10 Set screws with inner hexagon cone end	S/S 304	PCS	3	Paint the same color as the lamp body, white and water transfer lamp body with stainless steel color,1 fixed plastic plate,2 fixed diffusion cover	
8	Ø4 serrated lock washers exteral teeth	with zinc surface-plating	PCS	2		
9	Yellow and green earth wires (Φ4) L=140MM (with words), strip the wire by 10MM and dip it in tin	H05V-K 1+0.75MMP	PCS	1		
10	M4*8 Eleven slotted pan head self-squeezing screws	Hardness: 450HV0.3, Surface dacro	PCS	1	To fix the earth wires	Vith .
11	G18082 Inner cover sealing ring	silicone 50°,black	PCS	1	Ľ	With
12	G18082 inner cover	PA6+30%GF(blaak)	PCS	1		
13	M3+8 Eleven slotted pan head self-squeezing screws	Hardness: 450HV0.3, with zinc surface-plating	PCS	4	To fix the inner cover	
14	Ø5 shrinkable tube		METERS	0.03		
15	upper pressing button (Ø4 hole)	black PC	PCS	1		
16	BT2.9*8 Cross recessed pan head tapping and drilling screws	with zinc surface-plating	PCS	2	To fix the pressing button	
17	VED Single Core Cable (brown) L=160MM (Strip the wire 10MM from one end and dip it in tin. Strip the wire 3MM from the other end and dip it in tin)	H05V-K 0.75mm2	PCS	1	,	With G G G G G
18	VED single core cable (blue) L=160MM (<i>Strip the wire</i> 10MM from one end and dip it in tin. Strip the wire 3MM from the other end and dip it in tin.)	H05V-K 0.75mm2	PCS	1		With glue
19	terminal block OJ-831 Flat bottom and double click		PCS	1		
20	G18082 plastic tray	PA6+30%GF(black)	PCS	1		En 144 FE 144 151
21	17LG2 16476 G06444 protective ring	Silicone 50° natural color	PCS	1		
22	ST4.2*30 Cross recessed flat round head tapping screws	with zinc surface-plating	PCS	2	as the kit	
23	φ6+30 plastic expansion	φ6, HDPE	PCS	2	as the kit	
24	2.5MM hex key	nigrescence	PCS	1	as the kit	
					With	glue
	•	1	-		L	
						With glue